



Funcion aspirado-soplado
Suction-blowing function



Filtro HEPA
HEPA Filter



Tapón de vaciado de depósito
Tank drain plug



GY 10VC [Ⓢ]
Ref. GY10VC

GY 12VC [Ⓢ]
Ref. GY12VC

GY 16VC [Ⓢ]
Ref. GY16VC

	GY 10VC [Ⓢ] Ref. GY10VC	GY 12VC [Ⓢ] Ref. GY12VC	GY 16VC [Ⓢ] Ref. GY16VC
Capacidad del tanque / Tank capacity	10 l	20 l	30 l
Tanque / Tank	Plástico / Plastic	Acero inoxidable / Stainless steel	Acero inoxidable / Stainless steel
Potencia Máx. / Max. power	1000 W	1200 W	1600W-220V Y 1300W -120V
Cable / Power cord	3,5 m	3,5 m	5 m
Ruedas / Wheels	Rotatorias / Rotary	Rotatorias / Rotary	Rotatorias / Rotary

*Sincronizado disponible referencias: GY12VC-GY12VCS-GY16VC-GY16VCS. Para modelos a 120V (potencia máxima 800W)

PRO Equipo recomendado para uso profesional / Recommended equipment for professional use

LT Solo venta en LATAM / LATAM selling

Ⓢ Disponible versión S / Versión S available