



TALADROS / DRILLS



- Gatillo progresivo
- Dos velocidades
- Indicador de carga

- Progressive trigger
- Two speeds
- Charge indicator



GY 4520LD [Ⓢ]
Ref. GY4520LD

GY 1020LI [Ⓢ]
Ref. GY1020LI

GY1320LD [Ⓢ]
Ref. GY1320LD

| | | | |
|--|------------------|----------------------|---------------------|
| Voltage / Voltage | 20 V | 20 V | 20V |
| Batería / Battery | 2,0 Ah | 2,0 Ah | 2,0 Ah |
| Velocidad sin carga / No load speed | 0~400 / 1600 rpm | 0~400 rpm / 1300 rpm | 0-450/1,750rpm |
| Frecuencia de impacto / Impact frequency | 350-1500 rpm | 0-6000 / 0-19500 ipm | 0-9,000/0-32,400ipm |
| Par máximo / Max. Torque | | 27 NM | 50NM |
| Capacidad de taladrar acero / Drill capacity Steel | 13 mm | 10 mm | 13 mm |
| Capacidad de taladrar madera / Drill capacity Wood | 38 mm | 26 mm | 35 mm |
| Motor / Engine | Brushless | Brushless | - |

PRO Equipo recomendado para uso profesional / Recommended equipment for professional use

LT Solo venta en LATAM / LATAM shelling

Ⓢ Disponible versión S / Versión S available